



PRODUKTBROSCHYR

Spotlights

Version 1

Kontakta:

Joachim Schmidt

073-439 7444

joachim.schmidt@dolsch.se

Marko Dollsén

076-325 4919

marko.dollsen@dolsch.se

Spotlights

#	Art.nr.				
1	YM-TLD62-10W-M1 (dia: 62 mm)				
Teknisk specifikation					
LED-fabrikat:	Citizen Version 6	Drivdons-fabrikat:	Tridonic	Material i hus:	6063 borstad aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	250 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	120 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/38°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	10,59 W	Garanti:	5 år
#	Art.nr.				
2	YM-TLD62-15W-M1 (dia: 62 mm)				
Teknisk specifikation					
LED-fabrikat:	Citizen Version 6	Drivdons-fabrikat:	Tridonic	Material i hus:	6063 borstad aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	350 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	120 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/38°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	14,82 W	Garanti:	5 år
#	Art.nr.				
3	YM-TLD90-25W-M1 (dia: 90 mm)				
Teknisk specifikation					
LED-fabrikat:	Citizen Version 6	Drivdons-fabrikat:	Osram	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	600 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	120 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°/60°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	25,41 W	Garanti:	5 år



4	YM-TLD90-30W-M1 (dia: 90 mm)				
Teknisk specifikation					
LED-fabrikat:	Citizen Version 6	Drivdons-fabrikat:	Osram	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	750 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	120 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°/60°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	31,76 W	Garanti:	5 år
5	YM-TLD90-35W-M1 (dia: 90 mm)				
Teknisk specifikation					
LED-fabrikat:	Citizen Version 6	Drivdons-fabrikat:	Osram	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	800 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	120 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°/60°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	33,88 W	Garanti:	5 år
6	YM-TLD90-40W-M1 (dia: 100 mm)				
Teknisk specifikation					
LED-fabrikat:	Citizen Version 6	Drivdons-fabrikat:	Osram	Material i hus:	6063 borstad aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	950 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	120 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°/60°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	38,11 W	Garanti:	5 år



7	YM-TLD90-45W-M1 (dia: 110 mm)				
Teknisk specifikation					
LED-fabrikat:	Citizen Version 6	Drivdons-fabrikat:	Osram	Material i hus:	6063 borstad aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	1050 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	120 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°/60°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	44,47 W	Garanti:	5 år
8	YM-TLD90-50W-M1 (dia: 130 mm)				
Teknisk specifikation					
LED-fabrikat:	Citizen Version 6	Drivdons-fabrikat:	Osram	Material i hus:	6063 borstad aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	1200 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	120 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°/60°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	49,47 W	Garanti:	5 år



9	YM-TLD80-15W-M2 (dia:80 mm)				
Teknisk specifikation					
LED-fabrikat:	Epstar	Drivdons-fabrikat:	Designed by YM	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000 K	Output:	DC36 V	IP-klass:	IP44
CRI/Ra:	80/90/97	Ström:	350 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-100 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (3-trådig, 1-fas)	System-effekt:	14,82 W	Garanti:	3 år
10	YM-TLD80-20W-M2 (dia:80 mm)				
Teknisk specifikation					
LED-fabrikat:	Epstar	Drivdons-fabrikat:	Designed by YM	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP44
CRI/Ra:	80/90/97	Ström:	500 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-100 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (3-trådig, 1-fas)	System-effekt:	22,02 W	Garanti:	3 år
11	YM-TLD80-25W-M2 (dia:80 mm)				
Teknisk specifikation					
LED-fabrikat:	Epstar	Drivdons-fabrikat:	Designed by YM	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP44
CRI/Ra:	80/90/97	Ström:	600 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-100 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (3-trådig, 1-fas)	System-effekt:	25,41 W	Garanti:	3 år



12	YM-TLD88-30W-M2 (dia:88 mm)				
Teknisk specifikation					
LED-fabrikat:	Epstar	Drivdons-fabrikat:	Designed by YM	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP44
CRI/Ra:	80/90/97	Ström:	750 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-100 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (3-trådig, 1-fas)	System-effekt:	31,76 W	Garanti:	3 år
13	YM-TLD88-35W-M2 (dia:88 mm)				
Teknisk specifikation					
LED-fabrikat:	Epstar	Drivdons-fabrikat:	Designed by YM	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP44
CRI/Ra:	80/90/97	Ström:	800 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-100 lm/w @Ra80	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/36°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (3-trådig, 1-fas)	System-effekt:	33,76 W	Garanti:	3 år



14	YM-TLD90-20W-M3 (dia:90 mm)				
Teknisk specifikation					
LED-fabrikat:	Gen6 Citizen	Drivdons-fabrikat:	Power gear/Global	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP44
CRI/Ra:	80/90/97	Ström:	500 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-100 lm/w @Ra80/90/97	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/38°/60°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	20,58 W	Garanti:	5 år
15	YM-TLD90-25W-M3 (dia:90 mm)				
Teknisk specifikation					
LED-fabrikat:	Gen6 Citizen	Drivdons-fabrikat:	Power gear/Global	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP44
CRI/Ra:	80/90/97	Ström:	600 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-100 lm/w @Ra80/90/97	Input:	AC200-240 V	THD:	<15%
Ljusvinkel:	15°/24°/38°/60°	PF:	>0,9	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	24,58 W	Garanti:	5 år



16	YM-TLD90-20W-M4 (dia:90 mm)				
Teknisk specifikation					
LED-fabrikat:	Gen6 Citizen	Drivdons-fabrikat:	Boke/Osram	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	500 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-110 lm/w @Ra80	Input:	AC200-240 V	THD:	<12%
Ljusvinkel:	15°/24°/38°/60°	PF:	>0,95	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	22,02 W	Garanti:	5 år
17	YM-TLD90-25W-M4 (dia:90 mm)				
Teknisk specifikation					
LED-fabrikat:	Gen6 Citizen	Drivdons-fabrikat:	Boke/Osram	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	600 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-110 lm/w @Ra80	Input:	AC200-240 V	THD:	<12%
Ljusvinkel:	15°/24°/38°/60°	PF:	>0,95	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	25,41 W	Garanti:	5 år



18	YM-TLD90-30W-M4 (dia:90 mm)				
Teknisk specifikation					
LED-fabrikat:	Gen6 Citizen	Drivdons-fabrikat:	Boke/Osram	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	750 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-110 lm/w @Ra80	Input:	AC200-240 V	THD:	<12%
Ljusvinkel:	15°/24°/38°/60°	PF:	>0,95	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	31,76 W	Garanti:	5 år
19	YM-TLD90-35W-M4 (dia:90 mm)				
Teknisk specifikation					
LED-fabrikat:	Gen6 Citizen	Drivdons-fabrikat:	Boke/Osram	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	850 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-110 lm/w @Ra80	Input:	AC200-240 V	THD:	<12%
Ljusvinkel:	15°/24°/38°/60°	PF:	>0,95	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	36 W	Garanti:	5 år



20	YM-TLD110-40W-M4 (dia:110 mm)				
Teknisk specifikation					
LED-fabrikat:	Gen6 Citizen	Drivdons-fabrikat:	Boke/Osram	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	950 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-110 lm/w @Ra80	Input:	AC200-240 V	THD:	<12%
Ljusvinkel:	15°/24°/38°/60°	PF:	>0,95	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	40,23 W	Garanti:	5 år
21	YM-TLD110-45W-M4 (dia:110 mm)				
Teknisk specifikation					
LED-fabrikat:	Gen6 Citizen	Drivdons-fabrikat:	Boke/Osram	Material i hus:	ADC12 gjutet aluminium
CCT:	2700/3000/4000/5000 K	Output:	DC36 V	IP-klass:	IP20
CRI/Ra:	80/90/97	Ström:	1050 mA	Färg:	Svart/Vit/Silver
Lamp-effektivitet:	90-110 lm/w @Ra80	Input:	AC200-240 V	THD:	<12%
Ljusvinkel:	15°/24°/38°/60°	PF:	>0,95	Dimbar:	Ja
Track adapter:	Power Gear (4-trådig, 3-fas)	System-effekt:	44,47 W	Garanti:	5 år

